



FOR ATTENTION OF ALL BIDDERS

There is an important instruction regarding place of submission of Bid due to restricted movement of goods and services across the border, in view of page No 6 of this RFP, amending the clause 2 of this RFP to that Extent.

Appendices

A	: List of Stores	F	: Format of Certificate of Acceptance
B	: Technical Bid ('T' Bid)	G	: Undertaking Certificate
C	: Price Bid ('Q' Bid)	H	: Self Declaration Certificate
D	: EMD Bank Guarantee Format	J	: Test Certificate
E	: Performance Bank Guarantee Format		

INVITATION OF QUOTATION FOR SUPPLY OF CONSTRUCTIONAL STORES

Dear Sir/Madam,

INVITATION OF QUOTATION

1. This Project requires stores as per Appendix 'A' accordingly invites OTE for the purpose. The RFP can be downloaded from CPP Website : <https://eprocure.gov.in/epublish/app>. The consignor can submit their offer by downloading the enquiries and sending it by Speed Post/Courier/Hand.
2. Quotations are invited in physical form containing 'T'-Bid (Technical bid) as per Appx 'B' and 'Q'-Bid (Price Bid) as per Appx 'C' for the above items. Please note that quotation will be received by the Headquarters Chief Engineer (P) Dantak, C/o 99 APO upto 1700 Hrs (BST) on 01 Apr 2026. 'T'-Bid will be opened on 04 Apr 2026 at 1200 Hrs (BST). After opening of 'T'-Bid and its evaluation 'Q'-Bid will be opened for the successful bidders.
3. Firms or their duly authorized representative who have submitted their quotation and who wish to be present at the time of opening of quotation may visit the office of Headquarters Chief Engineer (P) Dantak, C/o 99 APO at the above mentioned time and date for viewing the quotation opening process.
4. Bidding procedure shall be single stage-two bid system and bid documents are to be prepared in two parts as under:-

Part-I (Technical Bid : 'T' Bid) at Appendix 'B'.
Part-II (Price Bid : 'Q' Bid) at Appendix 'C'.

5. **Part-I Technical Bid ('T' Bid)**

5.1. The technical bid comprising of the following details shall be forwarded in a separate envelope only by the OEM/ Authorised Dealer/Consignor duly mentioning the Name of the firm, Enquiry reference and date of opening etc on top of the envelope.

(a) Details such as Name of firm, Address Contact number GSTIN number, Email, PAN No and other Registration details with HQ DGBR / Project Dantak / Any other BRO Project / Ministry of Defence Govt of India / Govt of Bhutan as per format enclosed at Appendix 'B' to the enquiry be provided. OEM, PSUs and Authorised Dealer enlisted with Central Purchase Organization and National Small Industries Corporation also to provide details of their registration in Appendix 'B'.

(b) In case, if the firm is NOT enlisted / Registered with HQ DGBR or Project Dantak as a registered contractor/ consignor or with Ministry of Defence Govt of India or Govt of Bhutan or CPO or NSIC & Micro, Small and Medium Enterprises (MSMEs), then details of EMD alongwith original copy of EMD be provided as per Ser No 9 of Appx 'B'. PSUs, OEM/ Authorised dealer, Original Manufacturers in Bhutan/ India registered with Dantak/ HQ DGBR/ RGoB are exempted from submission of EMD on producing of necessary document/ certificates, in this regard.

(c) OEM/ Authorised Dealer/ Consignor should have completed minimum one supply order of the items to any Govt agency/BRO projects for last seven financial years. Copy of such supply order to be mandatorily enclosed with 'T' Bid failing which the firm will not be considered for opening of 'Q' Bid. Firms enlisted with Project Dantak for supply of same items need not to submit the copy of supply order of similar items.

5.2 Eligibility Criteria for Technical Evaluation

5.2.1 The manufacturers/ consignor who have submitted the following documents in their 'T' Bid will only be eligible technically and for opening of their 'Q' Bid:-

- (a) Fulfillment of criteria & submission of documents as laid down at Para 5.1.
- (b) Copy of tender documents duly signed and stamped on each page.
- (c) Complete details as per Appendix 'B' of enquiry
- (c) Registration details:
 - (i) Registration/Enlistment No
 - (ii) With whom registered/enlisted
 - (iii) Letter reference under which registered/enlisted. (Enclose copy)

Enlistment/ Registration details with HQ DGBR/ Project Dantak/ Ministry of Defence, GoI/ Govt of Bhutan/CPO/NSIC be clearly mentioned or EMD be submitted by non enlisted/non registered firms.

- (d) Original Manufacturers in Bhutan/India will have to submit EMD in case if they are not enlisted/ registered with HQ DGBR/Project Dantak or Government of Bhutan.
- (e) Copy of undertaking certificate duly signed (Format as per Para 13 (a) (iv) of RFP.
- (f) Manufacturers test certificate on the test as specified in Appx 'J'.
- (g) Copy of Importer- Exporter Code (IEC).

5.3. The bidder should meet all the technical evaluation criteria in order that the bid is considered to be technically responsive and the bidder qualifying to have its commercial bid opened. **BANNED FIRMS WILL NOT BE ENTERTAINED.**

5.4 REJECTION OF VENDORS

- (a) FIRMS APPLYING FOR THE SUBJECT TENDER WILL BE SCRUTINISED BASED ON THEIR PAST PERFORMANCE. BIDS OF FIRMS WHO HAVE SOUGHT TWO (02) OR MORE EXTENSION TO DELIVERY PERIOD WITH LD IN THE ONGOING (NON FRUCTIFIED) SUPPLY ORDERS ISSUED BY HQ CE (P) DANTAK WILL BE DISQUALIFIED.
- (b) VENDORS WHO ARE BANNED FOR PARTICIPATION IN THE TENDER ENQUIRY BY ANY GOVERNMENT DEPARTMENT IN INDIA/ BHUTAN NEED NOT APPLY. SCRUTINY OF VENDORS WILL BE DONE STRICTLY ON THE BASIS OF THEIR PERFORMANCE WITH GOVERNMENT DEPARTMENTS.
- (c) SELLER SHOULD SUBMIT ALL ABOVE DOCUMENTS WITH BID. IF ANY SELLER SUBMIT MISLEADING/FALSE INFORMATION IN BIDDING DOCUMENTS, SUCH SELLER WILL BE LIABLE TO BE DISQUALIFIED IN 'T' BID. NO REPRESENTATION IN THIS REGARDS WILL BE ENTERTAINED

6. Part-II Price Bid ('Q' Bid).

6.1 The price bid ('Q' Bid) shall be forwarded in a separate envelope by the OEM/ Authorised Dealer/ Consignor duly mentioning the name of the firm, Enquiry reference and date of opening on top of the envelope.

6.2. Part-II Price Bids ('Q' Bid). Price Bid shall be quoted by bidder as per the format attached as Appendix 'C'.

6.3. 'Q'-Bid evaluation. Price Bid of non qualified bidders, based on evaluation of 'T' Bid, will not be opened.

6.4 Price Bids shall only be furnished in attached format forming part of the bid documents.

Contd.....3/-



7. 'T' Bid and 'Q' Bid be submitted in **two separate envelopes** duly superscribed and both these sealed covers are to be put in a bigger cover which should be sealed and duly superscribed. **OEM/ Authorised Dealer/ Consignor** who offer the Enquiry documents of 'T' Bid and 'Q' Bid in a single envelope will be rejected. On top of both 'T' Bid and 'Q' Bid, details such as Name of **OEM/ Authorised Dealer/ Consignor** of the items, Enquiry Reference and date of opening etc will be mentioned clearly.
8. No conditional offer other than conditions mentioned above will be entertained.
9. All necessary licenses, consents and permissions for import/ export from Govt/ Semi Govt/ Civic agencies in India & Bhutan for the performance of obligations under this supply orders shall be arranged by the **OEM/ Authorised Dealer/ Consignor**.
10. The **OEM/ Authorised Dealer/ Consignor** shall provide and pay for usage of labour, utilities, transportation and other miscellaneous services necessary for proper execution and completion of supply order at the designated FOR.
11. The complete expenses on preparation and submission of quotation shall be borne by the firms and it shall have no claim on this account.

Earnest Money and Security Deposit.

12. **OEM/ Authorised Dealer/ Consignor** who are NOT enlisted as per Para 5.1 (b) of this RFP will have to submit Earnest Money of Amount in Rs **52,300/-** (Rupees fifty two thousand three hundred only) in the form of fixed Deposit receipt, or Bank guarantee from any of the commercial banks drawn in favour of Chief Engineer, Project Dantak payable at SBI Hasimara having validity/maturity period of Six Months and will be enclosed with Technical Bid. Earnest Money of un-successful **OEM/ Authorised Dealer/ Consignor** shall be returned to them immediately on placing of Supply Order. Format of EMD as per Appendix 'D' enclosed. **The MSME companies having valid Udyog Number, the EMD exemption as per DPM will be applicable.**

13. **Performance Bank Guarantee.** Performance Bank Guarantee in the form of Bank Guarantee should be submitted by your firm @ **5%** of the value of Supply Order amount within 30 days of receipt of the Supply Order, to **HQ 19 BRTF, Phuentsholing**. The Fixed Deposit Receipt or Bank Guarantee Bond be prepared having validity/maturity period of sixty days beyond the date of completion of all contractual obligations of the supplier including warranty obligation (Ref Rule-171 of GFR 2017). The PBG should be drawn in favour of **HQ 19 BRTF** payable at SBI, Hasimara. On receipt of Performance Bank Guarantee, the EMD will be returned to the firm. The Performance Bank Guarantee will be released after one month of release of completed payment against the supply order. If required, the extension of validity of Performance Bank Guarantee will be sought accordingly. Format of Performance Bank Guarantee as per Appendix 'E' enclosed. **In terms of Para 6.1.2 (i) of Manual of Procurement of Goods (updated June 2022), submission of PBG for an Supply Order amount upto twenty five (25) lakh is not required.**

(a) **Clause for Evaluation of L1.** To determine the L1, the quoted rates of consignor who have been found technically "Substantially Responsive". 'Q' Bid shall be evaluated as under:-

(i) **Evaluation method for arriving to L1 bidders will be total value wise evaluation.** Ranking of the commercial bid will be based on the lowest cost of sum total of all items to be delivered at **504 SS&TC (GREF) Phuentsholing (Bhutan)** which will be comprise of Basic Cost of items, Freight insurance, except levies, Taxes and Duties levied by Central/State Local Govts such as Octroi/Entry Tax, etc as quoted by the Bidder in his 'Q' Bid. All these elements shall mandatorily be indicated separately. Firms will have to quote for every item, failure to quote for any item will result in the disqualification of the firm in the 'Q' bid.

(ii) Any Taxes and Duties not mentioned clearly in 'Q'-Bid will not be counted and the Bidder shall not have any claim on account of such omissions on his part.

(iii) **GST/ Sales Tax are not applicable for Project Dantak.** For any query regarding exemption of GST on import of goods and services from India to Bhutan, kindly refer to the following websites for detail information.

(aa) www.cbec.gov.in/htdocs-cbec/gst/index.

(ab) www.cbec.gov.in/resources/htdocs-cbec/gst/notfctn-42-igst-rate-english.pdf.

(ac) www.cbec.gov.in/resources/htdocs-cbec/gst/notfctn-300CGST-rate-english.pdf.

(iv) **For Indian Consignor Only.** As supply to Project Dantak located outside India, no GST is applicable. Indian consignor / Bidder shall attach undertaking certificate as per the following format mandatorily :-

Contd.....4/-

UNDERTAKING CERTIFICATE

"It is certified that the goods / materials given in the Enquiry No 30003/DTK/19TF/Enq-58/E3ES dt 19 Mar 2026 of HQ CE (P) Dantak will be supplied by me / our firm as export and for use in Bhutan. It is declared that no GST cost has been included by me in the rates quoted in above mentioned enquiry".

Signature with date :
Name of the bidder :
Name of firm with address:

(v) Certificate on account of GST as per Rule No 16 (1) of IGST Act 2017 will be issued on receipt of stores as format of certificate is as given under:-

(aa) It is certified that the goods supplied by your firm against SO No 30003/DTK/19TF/SO.../E3ES dated _____ 2026 for the cost of Rs _____/- (Rupees _____ only) is a zero rated supply as per **GST Rule No 16 (1) of IGST Act 2017** as the goods were supplied as an export and to be used in Bhutan by this Project.

(ab) It is further certified that no amount was paid to your firm by this Project on account of GST

Consignee Unit

GST : ZERO RATED SUPPLY CERTIFICATE

(b) **Force Majeure Clause.** Should any force majeure circumstance arise, each of the contracting party shall be excused for the non fulfillment or for the delayed fulfillment of any of its contractual obligations, if the affected party within **14 days** of its occurrence informs in a written form the other party. Force majeure shall mean fires, floods, natural disasters or other acts such as war, turmoil, strikes, sabotage explosions, and quarantine restriction beyond the control of either party. **In the event of either party being rendered unable by Force Majeure to perform any obligations required to be performed by them under the purchase order the relative obligations of the party affected by such force majeure shall upon notification to the other party be suspended for the period during which force majeure event lasts. The cost and loss sustained by the either party shall be borne by the respective parties. If the force majeure conditions persist for a period exceeding 90 days the Purchaser reserves the right to cancel the purchase order in full or in part.**

Consignee, Delivery & Delivery Period.

14. Supply will have to be completed within **60 days** from the date of effect of supply order. The stores are required to be delivered as per Appendix 'A' attached to this enquiry to the **consignee unit 504 SS&TC (GREF), Phuentsholing (Bhutan)**. The responsibility for loading and unloading of stores including transit loss shall rest with the consignor. The firm who are unable to supply the desired items within original delivery period due to any reason and are contemplating/seeking extension of original delivery period must send their request by email giving detailed reason for seeking original delivery period extension and the request should reach seven clear working days before expiring of original delivery period failing which the supply order will be considered to be terminated and firm will be responsible for the same.

Price Adjustment.

15. **Prices.** All the rates/prices mentioned in the purchase order shall remain firm throughout the delivery/ shipment of the goods/ performance of the services. Price escalation on any scores whatsoever due to increase in any statutory taxes or duties will NOT be entertained.

Manufacturer/ Authorised dealer (Consignor/ Distributor).

16. In case your firm is an **original manufacturer of the product or an authorized dealer**, a certificate to this effect shall be enclosed alongwith product catalogue and company price list, Discount, if any offered thereon shall be specified clearly. If the product is proprietary in nature, certificate to this effect that the firm is sole **OEM/ Authorised Dealer/ Consignor** of the product shall be enclosed with the offer.

Contd.....5/-


Freight/ Warranty

17. **Freight** Packaging and freight will be complete responsibility of the consignor. Damages/ losses in transit shall be the responsibility of the consignor upto the delivery location specified by the respective consignees. No Defence vehicles will be provided to transport the stores. Stores will be securely packed without any additional cost to the Govt to avoid losses or damages during transit so as to reach this consignee, in perfect serviceable and fit for use condition. The consignor shall remain responsible for adequacy of packages during transit. The packages shall be marked with the Supply order and other necessary details for easy identification at the consignee's end. The consignor will be responsible for unloading at for and to ensure that the stores are delivered in sound condition without any damage.

18. **Warranty/Guarantee.** The stores supplied against the supply order shall bear a warranty against defective materials for a period of **one years** or as specified by the company/ consignor/firm (whichever is higher) from the date of completion of the supply order. In case of manufacturing failure or defect in any component within the warranty period, the consignee shall inform the consignor for joint inspection. Within a period of one week of the receipt of such information, the rejected material shall be removed and replaced by the consignor at the site at his own expense and no extra payment shall be made on this account. All stores to be supplied should be free from all defects and faults in material workmanship and manufacture. They should be of the highest grade and consistent with the established and generally accepted standards for material of the type used and in full conformity with the specifications, drawings or samples and shall, if operable, operate properly. The Consignor shall be bound to furnish a clear written warranty regarding the same. In the event of the ultimate consignee in Bhutan not finding the stores in accordance with the order, the Consignor will be required to replace them free of cost inclusive of all freight and handling charges. Such replacement will be done within **ninety days** to the claim report raised by the Consignee. These standard conditions will also apply in respect of replaced stores.

TERMINATION OF PURCHASE ORDER

19. **Termination for Non-performance.** The Purchaser without prejudice to any other remedy for breach of purchase order, by giving a written notice for non-performance to the Seller/consignor, may terminate the purchase order in whole or in part for following reasons:-

- 
- (a) When the supplier fails to honour any part of the supply order including failure to deliver the supply order stores/ render services in time.
 - (b) When the contractor is found to have made any false or fraudulent declaration or statement to get the supply order or he is found to be indulging in unethical or unfair trade practices.
 - (c) When both parties mutually agree to terminate the supply order.
 - (d) When the item offered by the supplier repeatedly fails in the inspection and/or the supplier is not in a position to either rectify the defects or offer items conforming to the stores quality standards.
 - (e) Any special circumstances, which must be recorded to justify the cancellation or termination of a supply order.
 - (f) If the Seller/ consignor, in the either of the above condition, does not cure his failure within a stipulated period of 30 days (or such a longer period may authorize by the Purchaser in writing) after receipt of notice of non-performance form the Purchaser.

Contact Address.

20. For any further information/clarification on the subject the following Officer may be contacted during the office hours (i.e. 0830 Hrs to 1700 Hrs BST except Sunday/Holidays):-

SO-1 (Res)
Headquarters
Chief Engineer
Project Dantak
Tele No .009752351082/86/88
FAX No . 009752351285

21. The accepting officer does not bind himself to accept the lowest quotation or any other quotation and reserves the right to accept or reject any of the quotation either in part or in full without assigning any reasons what so ever thereto.

22. No purchase against this enquiry is guaranteed.
23. The quantities of stores given is/are guidelines and may be decreased upto minus (-) 10% according to our requirement at the time of placing of supply order.
24. Quotation received after the expiry of time and date specified in **Para 02** above will not be entertained.
25. Payment will be made on receipt of stores in full as there is no provision for making advance payment. **NO PART PAYMENT WILL BE APPLICABLE.**
26. **Repeat Order Clause.** The Consignee may order upto 50% qty of SO within six months from the date of successful completion of the supply against this contract and at the same cost, terms and conditions of the contract. The Consignor is bound to supply the material.
27. **Sample Approval.** If desired by consignee, the firm shall produce one sample of the item for approval to the consignee within 20 days of this Supply Order only the approved samples will be supplied in bulk as per the quantity given in Supply Order. Samples may be approved by producing actual samples or through a catalogue of desired make as per SO. Date of approval of sample will have no effect to the delivery period mentioned in the RFP/ Supply Order.
28. **Inspection.** The stores supplied may be inspected by the BOO detailed by the CFA or his authorized rep at time of delivery and should be strictly according to the specifications provided in the supply order. In case the items are found not according to specifications/satisfaction of the Inspecting Officer, the stores are liable to be rejected and will have to be replaced **within 30 days** without any additional cost by the consignor /firms.
29. **LD.** The consignor shall be liable to pay liquidated damages and not as a penalty, a sum equivalent to ½% (Half Percent) of the contract/supply order price per week of delay or part thereof. The consignor liability of liquidated damages shall not exceed maximum of 10% (Ten percent) of the contract price. If the delivery is delayed beyond 10 weeks, the consignee may at his own option, terminate the contract / supply order.
30. **Validity.** The rates should be valid for 120 days wef the date of submission of the offer.
31. **Manufacturer test Certificate.** Manufacturer test certificate for the parameters/specifications as given out in **Appx 'J'** of RFP will be submitted by the successful bidder for each lot of material being supplied. In case the test results do not meet the required specifications, the stores will be rejected. No representation in this regard will be entertained.
32. Mentioning of GSTIN Nos and quoting rates in words is compulsory, without which enquiry will not be considered for placing supply order. Clear description/specification of items is also mandatory.
33. Rates be quoted for items as per specification in enquiry only.
34. **EMD.** In case non supply of stores against this supply order, then EMD/ Performance Bank Guarantee Bank Guarantee will be ceased by department.
35. Acceptance certificate forward to HQ CE (P) Dantak against this enquiry Supply Order No 30003/DTK/19TF/SO-_____/E3ES dated ____/____/ 2026. Format as per **Appx 'F'**.
36. **TAXES.** ANY TAXES TO BE LEVIED / EXEMPTION TO BE GRANTED WILL BE APPLICABLE AS PER THE NEW GST RULES 2026 IMPLEMENTED WITH EFFECT FROM 01 JAN 2026 IN KINGDOM OF BHUTAN & PROCEDURES INVOLVED THEREBY.



Contd.....7/-

37. In addition to the existing facility/provision of receiving bids at HQ CE (P) Dantak and as mentioned in clause 2 of this RFP, a facility has been created on Indian side border town of Jaigaon to facilitate submission of bids by Indian Bidders. The bidders can exercise following option and address:-

(a) **Existing facility at HQ CE (P) Dantak Thimphu:-**

(i) **If sending bids by post:-**

HQ CE (P) Dantak
PIN - 931 708
C/o 99 APO

(ii) **Manual Submission** - Dropping of bids in tender Box kept in HQ CE (P) Dantak premises.

(b) **Additional facility at Jaigaon:-**

(i) **If sending bids by post:-**

OIC Liaison Cell
Supervisor Mess, HQ 19 BRTF (GREF)
Jaigaon (W.B.)
PIN - 736 182
Contact details/ Phone No - 9970889254

(ii) **Manual submission** - Dropping of bids in tender Box kept in Supervisor Mess, HQ 19 BRTF (GREF) Jaigaon (W.B).

Address:-

OIC Liaison Cell
Supervisor Mess, HQ 19 BRTF (GREF)
Jaigaon (W.B.)
PIN - 736 182
Contact details/ Phone No - 9970889254

Please take acknowledgement from OIC Liaison Cell in case of manual submission at Jaigaon.

Note:- Last date and time for submission of bids will be same for both the location and bids from both the places will be collected and opened on fixed date by the nominated BOO at HQ CE (P) Dantak.



Your's faithfully,

(Manoj Kumar)
EE (Civ)
Offg SO-1 (Res)
for Chief Engineer

Contd.....8/-

LIST OF STORES

HQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026

Ser No	Nomenclature	A/U	Qty																																																																																									
Stores to be supplied to 504 SS&TC (GREF), Phuentsholing (Bhutan)																																																																																												
1	<p>Geocell incl all accessories like TRA keys and ATRA clips. Specifications of Geocell to be as given below:-</p> <table border="1"> <thead> <tr> <th colspan="4">PHYSICAL PROPERTIES</th> </tr> <tr> <th>Parameter</th> <th>Units</th> <th colspan="2">Minimum Required Value</th> </tr> </thead> <tbody> <tr> <td>Cell Depth</td> <td>mm</td> <td colspan="2">200</td> </tr> <tr> <td>Weld Spacing</td> <td>mm</td> <td colspan="2">356</td> </tr> <tr> <td rowspan="2">Expanded cell dimension</td> <td>Width</td> <td>mm</td> <td>259</td> </tr> <tr> <td>Length</td> <td>mm</td> <td>224</td> </tr> <tr> <td rowspan="2">Expanded Dimension</td> <td>Width</td> <td>m</td> <td>2.59</td> </tr> <tr> <td>Length</td> <td>m</td> <td>6.50</td> </tr> <tr> <td>Expanded section area</td> <td>m²</td> <td colspan="2">16.8</td> </tr> <tr> <th colspan="4">PERFORMANCE PROPERTIES</th> </tr> <tr> <th>Parameter</th> <th>Test method</th> <th>Unit</th> <th>Minimum Required Value</th> </tr> <tr> <td>Density</td> <td>IS 13360 (Part 3)/ ASTM D 1505</td> <td>g/cm³</td> <td>0.9</td> </tr> <tr> <td>Environmental stress crack resistance (ESCR), Modulus</td> <td>IS 17483/ ASTM D 1693</td> <td>Hours</td> <td>≥ 5000</td> </tr> <tr> <td>Carbon black content</td> <td>IS 2530/ ASTM D 1603</td> <td>%</td> <td>2</td> </tr> <tr> <td>Cell wall thickness</td> <td>IS 13162 (Part 3)/ ASTM D 5199</td> <td>mm</td> <td>1.20-1.25</td> </tr> <tr> <td>Perforation Area</td> <td>-</td> <td>%</td> <td>10</td> </tr> <tr> <td>Seam Peel-Strength Text (N per 25 mm of cell depth)</td> <td>-</td> <td>N</td> <td>350</td> </tr> <tr> <td>Standard oxidative induction time</td> <td>ISO 11357-6</td> <td>minutes</td> <td>100</td> </tr> <tr> <td>High pressure oxidative induction time</td> <td>ASTM D 5885</td> <td>minutes</td> <td>400</td> </tr> <tr> <td>Make</td> <td colspan="3">Geosys/ Techfab/ Geoquest/ Macceferri/ Terrain Geoinfra</td> </tr> </tbody> </table>	PHYSICAL PROPERTIES				Parameter	Units	Minimum Required Value		Cell Depth	mm	200		Weld Spacing	mm	356		Expanded cell dimension	Width	mm	259	Length	mm	224	Expanded Dimension	Width	m	2.59	Length	m	6.50	Expanded section area	m ²	16.8		PERFORMANCE PROPERTIES				Parameter	Test method	Unit	Minimum Required Value	Density	IS 13360 (Part 3)/ ASTM D 1505	g/cm ³	0.9	Environmental stress crack resistance (ESCR), Modulus	IS 17483/ ASTM D 1693	Hours	≥ 5000	Carbon black content	IS 2530/ ASTM D 1603	%	2	Cell wall thickness	IS 13162 (Part 3)/ ASTM D 5199	mm	1.20-1.25	Perforation Area	-	%	10	Seam Peel-Strength Text (N per 25 mm of cell depth)	-	N	350	Standard oxidative induction time	ISO 11357-6	minutes	100	High pressure oxidative induction time	ASTM D 5885	minutes	400	Make	Geosys/ Techfab/ Geoquest/ Macceferri/ Terrain Geoinfra			Sqm	4069.80											
PHYSICAL PROPERTIES																																																																																												
Parameter	Units	Minimum Required Value																																																																																										
Cell Depth	mm	200																																																																																										
Weld Spacing	mm	356																																																																																										
Expanded cell dimension	Width	mm	259																																																																																									
	Length	mm	224																																																																																									
Expanded Dimension	Width	m	2.59																																																																																									
	Length	m	6.50																																																																																									
Expanded section area	m ²	16.8																																																																																										
PERFORMANCE PROPERTIES																																																																																												
Parameter	Test method	Unit	Minimum Required Value																																																																																									
Density	IS 13360 (Part 3)/ ASTM D 1505	g/cm ³	0.9																																																																																									
Environmental stress crack resistance (ESCR), Modulus	IS 17483/ ASTM D 1693	Hours	≥ 5000																																																																																									
Carbon black content	IS 2530/ ASTM D 1603	%	2																																																																																									
Cell wall thickness	IS 13162 (Part 3)/ ASTM D 5199	mm	1.20-1.25																																																																																									
Perforation Area	-	%	10																																																																																									
Seam Peel-Strength Text (N per 25 mm of cell depth)	-	N	350																																																																																									
Standard oxidative induction time	ISO 11357-6	minutes	100																																																																																									
High pressure oxidative induction time	ASTM D 5885	minutes	400																																																																																									
Make	Geosys/ Techfab/ Geoquest/ Macceferri/ Terrain Geoinfra																																																																																											
2	<p>Geocomposite (710 GSM). Specifications of Geocomposite to be as given below:-</p> <table border="1"> <thead> <tr> <th colspan="4">MECHANICAL PROPERTIES</th> </tr> <tr> <th>Properties</th> <th>Test method</th> <th>Unit</th> <th>Minimum Required Value</th> </tr> </thead> <tbody> <tr> <td colspan="4">Drainage Core</td> </tr> <tr> <td>Type of Product</td> <td colspan="3">HDPE Geonet UV stabilized, comprising of integrally connected set of parallel strands</td> </tr> <tr> <td>Thickness at 2 Kpa</td> <td>EN ISO-9863</td> <td>mm</td> <td>4.5</td> </tr> <tr> <td>Mass per unit area</td> <td>EN ISO-9864</td> <td>g/m²</td> <td>710</td> </tr> <tr> <td>Tensile strength</td> <td>EN ISO-10319</td> <td>kN/m</td> <td>16</td> </tr> <tr> <td>CBR Puncture resistance</td> <td>EN ISO-12236</td> <td>N</td> <td>3000</td> </tr> <tr> <td rowspan="2">In Plane permeability</td> <td rowspan="2">Hydraulic Gradient, i=1 at 100 kPa pressure</td> <td rowspan="2">EN ISO-12958</td> <td rowspan="2">l/(m.s)</td> </tr> <tr> <td>0.45</td> </tr> <tr> <td colspan="4">Filter Layer</td> </tr> <tr> <td>Type of product</td> <td colspan="3">Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core</td> </tr> <tr> <td>Static Puncture Resistance</td> <td>EN ISO-12236</td> <td>N</td> <td>1200</td> </tr> <tr> <td>Flow Rate</td> <td>ASTM D4491</td> <td>l/m²/s</td> <td>50</td> </tr> <tr> <td>Characteristic Opening Size</td> <td>EN ISO-12956</td> <td>mm</td> <td>0.22</td> </tr> <tr> <td>Retained Properties after UV exposure</td> <td>ASTM D4355</td> <td>%</td> <td>70</td> </tr> <tr> <td colspan="4">Composite Drain</td> </tr> <tr> <td>Type of Product</td> <td colspan="3">Geonet + Filter Geotextile on both side</td> </tr> <tr> <td>Width</td> <td>-</td> <td>m</td> <td>2</td> </tr> <tr> <td>Length</td> <td>-</td> <td>m</td> <td>20/25/50</td> </tr> <tr> <td colspan="4">Filter Geotextile</td> </tr> <tr> <td>Permittivity</td> <td>ASTM D 4491</td> <td>S⁻¹</td> <td>1.0</td> </tr> <tr> <td>Make</td> <td colspan="3">Geosys/ Techfab/ Geoquest/ Macceferri/ Terrain Geoinfra</td> </tr> </tbody> </table>	MECHANICAL PROPERTIES				Properties	Test method	Unit	Minimum Required Value	Drainage Core				Type of Product	HDPE Geonet UV stabilized, comprising of integrally connected set of parallel strands			Thickness at 2 Kpa	EN ISO-9863	mm	4.5	Mass per unit area	EN ISO-9864	g/m ²	710	Tensile strength	EN ISO-10319	kN/m	16	CBR Puncture resistance	EN ISO-12236	N	3000	In Plane permeability	Hydraulic Gradient, i=1 at 100 kPa pressure	EN ISO-12958	l/(m.s)	0.45	Filter Layer				Type of product	Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core			Static Puncture Resistance	EN ISO-12236	N	1200	Flow Rate	ASTM D4491	l/m ² /s	50	Characteristic Opening Size	EN ISO-12956	mm	0.22	Retained Properties after UV exposure	ASTM D4355	%	70	Composite Drain				Type of Product	Geonet + Filter Geotextile on both side			Width	-	m	2	Length	-	m	20/25/50	Filter Geotextile				Permittivity	ASTM D 4491	S ⁻¹	1.0	Make	Geosys/ Techfab/ Geoquest/ Macceferri/ Terrain Geoinfra			Sqm	495
MECHANICAL PROPERTIES																																																																																												
Properties	Test method	Unit	Minimum Required Value																																																																																									
Drainage Core																																																																																												
Type of Product	HDPE Geonet UV stabilized, comprising of integrally connected set of parallel strands																																																																																											
Thickness at 2 Kpa	EN ISO-9863	mm	4.5																																																																																									
Mass per unit area	EN ISO-9864	g/m ²	710																																																																																									
Tensile strength	EN ISO-10319	kN/m	16																																																																																									
CBR Puncture resistance	EN ISO-12236	N	3000																																																																																									
In Plane permeability	Hydraulic Gradient, i=1 at 100 kPa pressure	EN ISO-12958	l/(m.s)																																																																																									
				0.45																																																																																								
Filter Layer																																																																																												
Type of product	Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core																																																																																											
Static Puncture Resistance	EN ISO-12236	N	1200																																																																																									
Flow Rate	ASTM D4491	l/m ² /s	50																																																																																									
Characteristic Opening Size	EN ISO-12956	mm	0.22																																																																																									
Retained Properties after UV exposure	ASTM D4355	%	70																																																																																									
Composite Drain																																																																																												
Type of Product	Geonet + Filter Geotextile on both side																																																																																											
Width	-	m	2																																																																																									
Length	-	m	20/25/50																																																																																									
Filter Geotextile																																																																																												
Permittivity	ASTM D 4491	S ⁻¹	1.0																																																																																									
Make	Geosys/ Techfab/ Geoquest/ Macceferri/ Terrain Geoinfra																																																																																											

Registration No. of Firm
TIN No. of Firm
Firm Seal
Fax & Tele No.



(Signature)
(Manoj Kumar)
EE (Civ)
Offg SO -1 (Res)
for Chief Engineer

Contd.....9/-

TECHNICAL BID ('T' BID)

HQ CE (P) Dantak Enq No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026
(As per Clause Para 5)


PARTICULAR OF FIRM		
SER NO	ITEMS	DETAILS
1.	Name of firms	
2.	Legal Status of the firm	Individual company (Incorporated un-incorporated)/ Partnership firm / public limited
3.	Address	
4.	Contact Telephone, Mobile & Fax No	
5.	E-mail address	
6.	GSTIN No	
7.	PAN No	
8.	Registration details :-	
	(a) Registration/Enlistment No.	
	(b) With whom registered /enlisted	
	(c) Letter ref under which registered/enlisted. (Enclose copy)	
9.	EMD (For unregistered consignor / firm only) EMD in the form of cheque is not acceptable. EMD be submitted in the form of Fixed Deposit Receipt or Bank Guarantee only	Amount Rs 52,300/- Fixed Deposit Receipt or Bank Guarantee Number _____ Dated : _____
Date		(Signature of authorized rep of firm with seal)

Note:

1. Firm enlisted with HQ CE (Project) Dantak need not enclose photocopy of GSTIN No, PAN No and copy of letters reference under which registered. Rest all firms should enclose relevant photocopies.
2. Firms should enclose all relevant documents as mentioned under Para 5 of this Enquiry in addition to the above details, failing which the firm will be rejected during 'T' Bid evaluation.

(Signature of consignor)




 (Manoj Kumar)
 EE (Civ)
 Offg SO-1 (Res)
 for Chief Engineer

Contd..... 10/-

PRICE BID ('Q' BID)
HQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026

Ser No	Nomenclature	A/U	Qty	Basic Price	Total Amt																																																																																																					
Stores to be supplied to 504 SS&TC (GREF), Phuentsholing (Bhutan)																																																																																																										
1	Geocell incl all accessories like TRA keys and ATRA clips. Specifications of Geocell to be as given below:- <table border="1"> <thead> <tr> <th colspan="4">PHYSICAL PROPERTIES</th> </tr> <tr> <th>Parameter</th> <th>Units</th> <th colspan="2">Minimum Required Value</th> </tr> </thead> <tbody> <tr> <td>Cell Depth</td> <td>mm</td> <td colspan="2">200</td> </tr> <tr> <td>Weld Spacing</td> <td>mm</td> <td colspan="2">356</td> </tr> <tr> <td rowspan="2">Expanded cell dimension</td> <td>Width</td> <td>mm</td> <td>259</td> </tr> <tr> <td>Length</td> <td>mm</td> <td>224</td> </tr> <tr> <td rowspan="2">Expanded Dimension</td> <td>Width</td> <td>m</td> <td>2.59</td> </tr> <tr> <td>Length</td> <td>m</td> <td>6.50</td> </tr> <tr> <td>Expanded section area</td> <td>m²</td> <td colspan="2">16.8</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="4">PERFORMANCE PROPERTIES</th> </tr> <tr> <th>Parameter</th> <th>Test method</th> <th>Unit</th> <th>Minimum Required Value</th> </tr> </thead> <tbody> <tr> <td>Density</td> <td>IS 13360 (Part 3)/ ASTM D 1505</td> <td>g/cm³</td> <td>0.9</td> </tr> <tr> <td>Environmental stress crack resistance (ESCR), Modulus</td> <td>IS 17483/ ASTM D 1693</td> <td>Hours</td> <td>≥ 3000</td> </tr> <tr> <td>Carbon black content</td> <td>IS 2530/ ASTM D 1603</td> <td>%</td> <td>2</td> </tr> <tr> <td>Cell wall thickness</td> <td>IS 13162 (Part 3)/ ASTM D 5199</td> <td>mm</td> <td>1.20-1.25</td> </tr> <tr> <td>Perforation Area</td> <td>-</td> <td>%</td> <td>10</td> </tr> <tr> <td>Seam Peel-Strength Text (N per 25 mm of cell depth)</td> <td>-</td> <td>N</td> <td>350</td> </tr> <tr> <td>Standard oxidative induction time</td> <td>ISO 11357-6</td> <td>minutes</td> <td>100</td> </tr> <tr> <td>High pressure oxidative induction time</td> <td>ASTM D 5885</td> <td>minutes</td> <td>400</td> </tr> </tbody> </table> Make Geosys/ Techfab/ Geoquest/ Maccefferri/ Terrain Geoinfra	PHYSICAL PROPERTIES				Parameter	Units	Minimum Required Value		Cell Depth	mm	200		Weld Spacing	mm	356		Expanded cell dimension	Width	mm	259	Length	mm	224	Expanded Dimension	Width	m	2.59	Length	m	6.50	Expanded section area	m ²	16.8		PERFORMANCE PROPERTIES				Parameter	Test method	Unit	Minimum Required Value	Density	IS 13360 (Part 3)/ ASTM D 1505	g/cm ³	0.9	Environmental stress crack resistance (ESCR), Modulus	IS 17483/ ASTM D 1693	Hours	≥ 3000	Carbon black content	IS 2530/ ASTM D 1603	%	2	Cell wall thickness	IS 13162 (Part 3)/ ASTM D 5199	mm	1.20-1.25	Perforation Area	-	%	10	Seam Peel-Strength Text (N per 25 mm of cell depth)	-	N	350	Standard oxidative induction time	ISO 11357-6	minutes	100	High pressure oxidative induction time	ASTM D 5885	minutes	400	Sqm	4069.80																													
PHYSICAL PROPERTIES																																																																																																										
Parameter	Units	Minimum Required Value																																																																																																								
Cell Depth	mm	200																																																																																																								
Weld Spacing	mm	356																																																																																																								
Expanded cell dimension	Width	mm	259																																																																																																							
	Length	mm	224																																																																																																							
Expanded Dimension	Width	m	2.59																																																																																																							
	Length	m	6.50																																																																																																							
Expanded section area	m ²	16.8																																																																																																								
PERFORMANCE PROPERTIES																																																																																																										
Parameter	Test method	Unit	Minimum Required Value																																																																																																							
Density	IS 13360 (Part 3)/ ASTM D 1505	g/cm ³	0.9																																																																																																							
Environmental stress crack resistance (ESCR), Modulus	IS 17483/ ASTM D 1693	Hours	≥ 3000																																																																																																							
Carbon black content	IS 2530/ ASTM D 1603	%	2																																																																																																							
Cell wall thickness	IS 13162 (Part 3)/ ASTM D 5199	mm	1.20-1.25																																																																																																							
Perforation Area	-	%	10																																																																																																							
Seam Peel-Strength Text (N per 25 mm of cell depth)	-	N	350																																																																																																							
Standard oxidative induction time	ISO 11357-6	minutes	100																																																																																																							
High pressure oxidative induction time	ASTM D 5885	minutes	400																																																																																																							
2	Geocomposite (710 GSM). Specifications of Geocomposite to be as given below:- <table border="1"> <thead> <tr> <th colspan="5">MECHANICAL PROPERTIES</th> </tr> <tr> <th>Properties</th> <th>Test method</th> <th>Unit</th> <th colspan="2">Minimum Required Value</th> </tr> </thead> <tbody> <tr> <td colspan="5">Drainage Core</td> </tr> <tr> <td>Type of Product</td> <td colspan="4">HDPE Geonet UV stabilized, comprising of integrally connected set</td> </tr> <tr> <td>Thickness at 2 Kpa</td> <td>EN ISO-9863</td> <td>mm</td> <td colspan="2">4.5</td> </tr> <tr> <td>Mass per unit area</td> <td>EN ISO-9864</td> <td>g/m²</td> <td colspan="2">710</td> </tr> <tr> <td>Tensile strength</td> <td>EN ISO-10319</td> <td>kN/m</td> <td colspan="2">16</td> </tr> <tr> <td>CBR Puncture resistance</td> <td>EN ISO-12236</td> <td>N</td> <td colspan="2">3000</td> </tr> <tr> <td rowspan="2">In Plane permeability</td> <td rowspan="2">Hydraulic Gradient, i=1 at 100 kPa pressure</td> <td rowspan="2">EN ISO-12958</td> <td rowspan="2">l/(m.s)</td> <td>0.55</td> </tr> <tr> <td>0.45</td> </tr> <tr> <td colspan="5">Filter Layer</td> </tr> <tr> <td>Type of product</td> <td colspan="4">Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core</td> </tr> <tr> <td>Static Puncture Resistance</td> <td>EN ISO-12236</td> <td>N</td> <td colspan="2">1200</td> </tr> <tr> <td>Flow Rate</td> <td>ASTM D4491</td> <td>l/m²/s</td> <td colspan="2">50</td> </tr> <tr> <td>Characteristic Opening Size</td> <td>EN ISO-12956</td> <td>mm</td> <td colspan="2">0.22</td> </tr> <tr> <td>Retained Properties after UV exposure</td> <td>ASTM D4355</td> <td>%</td> <td colspan="2">70</td> </tr> <tr> <td colspan="5">Composite Drain</td> </tr> <tr> <td>Type of Product</td> <td colspan="4">Geonet + Filter Geotextile on both side</td> </tr> <tr> <td>Width</td> <td>-</td> <td>m</td> <td colspan="2">2</td> </tr> <tr> <td>Length</td> <td>-</td> <td>m</td> <td colspan="2">20/25/50</td> </tr> <tr> <td>Permittivity</td> <td>ASTM D 4491</td> <td>S⁻¹</td> <td colspan="2">1.0</td> </tr> </tbody> </table> Make Geosys/ Techfab/ Geoquest/ Maccefferri/ Terrain Geoinfra	MECHANICAL PROPERTIES					Properties	Test method	Unit	Minimum Required Value		Drainage Core					Type of Product	HDPE Geonet UV stabilized, comprising of integrally connected set				Thickness at 2 Kpa	EN ISO-9863	mm	4.5		Mass per unit area	EN ISO-9864	g/m ²	710		Tensile strength	EN ISO-10319	kN/m	16		CBR Puncture resistance	EN ISO-12236	N	3000		In Plane permeability	Hydraulic Gradient, i=1 at 100 kPa pressure	EN ISO-12958	l/(m.s)	0.55	0.45	Filter Layer					Type of product	Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core				Static Puncture Resistance	EN ISO-12236	N	1200		Flow Rate	ASTM D4491	l/m ² /s	50		Characteristic Opening Size	EN ISO-12956	mm	0.22		Retained Properties after UV exposure	ASTM D4355	%	70		Composite Drain					Type of Product	Geonet + Filter Geotextile on both side				Width	-	m	2		Length	-	m	20/25/50		Permittivity	ASTM D 4491	S ⁻¹	1.0		Sqm	495		
MECHANICAL PROPERTIES																																																																																																										
Properties	Test method	Unit	Minimum Required Value																																																																																																							
Drainage Core																																																																																																										
Type of Product	HDPE Geonet UV stabilized, comprising of integrally connected set																																																																																																									
Thickness at 2 Kpa	EN ISO-9863	mm	4.5																																																																																																							
Mass per unit area	EN ISO-9864	g/m ²	710																																																																																																							
Tensile strength	EN ISO-10319	kN/m	16																																																																																																							
CBR Puncture resistance	EN ISO-12236	N	3000																																																																																																							
In Plane permeability	Hydraulic Gradient, i=1 at 100 kPa pressure	EN ISO-12958	l/(m.s)	0.55																																																																																																						
				0.45																																																																																																						
Filter Layer																																																																																																										
Type of product	Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core																																																																																																									
Static Puncture Resistance	EN ISO-12236	N	1200																																																																																																							
Flow Rate	ASTM D4491	l/m ² /s	50																																																																																																							
Characteristic Opening Size	EN ISO-12956	mm	0.22																																																																																																							
Retained Properties after UV exposure	ASTM D4355	%	70																																																																																																							
Composite Drain																																																																																																										
Type of Product	Geonet + Filter Geotextile on both side																																																																																																									
Width	-	m	2																																																																																																							
Length	-	m	20/25/50																																																																																																							
Permittivity	ASTM D 4491	S ⁻¹	1.0																																																																																																							

Registration No. of Firm
TIN No. of Firm
Firm Seal
Fax & Tele No.



(Manoj Kumar)
EE (Civ)
Offg SO -1 (Res)
for Chief Engineer

Contd..... 11/-

EMD BANK GUARANTEE FORMAT**HQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026**

Whereas(hereinafter called the "Bidder") has submitted their offer against enquiry No 30003/DTK/19TF/ENQ-58/E3ES dated 19 Mar 2026 for the supply of stores (hereinafter called the "Bid") against the Buyer's Request for proposal No 30003/DTK/19TF/SO-/E3ES dated ___/___/2026 KNOW ALL MEN by these presents that weof.....having our registered office at.....are bound unto.....(hereinafter called the "Buyer) in the sum offor which payment will and truly to be made to the said Buyer, the Bank binds itself, its successors and assigns by these presents. Sealed with the Common Seal of the said Bank this day of ___/___/ie 2026.

The conditions of obligations are:-

1. If the Bidder withdraws or amends, impairs or derogates from the Bid in any respect within the period of validity of this tender.
2. If the Bidder having been notified of the acceptance of his tender by the Buyer during the period of its validity.
3. If the Bidder fails to furnish the Performance Bank Guarantee for the due performance of the supply order.
4. Fails or refuses to accept/execute the supply order.

WE undertake to pay the Buyer up to the above amount upon receipt of its first written demand, without the Buyer having to substantiate its demand, provided that in its demand the Buyer will note that the amount claimed by it is due to it owing to the occurrence of one or both the two conditions, specifying the occurred condition or conditions. This guarantee will remain in force upto and including 90 days after the period of tender validity and any demand in respect thereof should reach the Bank not later than the above date.

.....

 (Signature of the authorized officer of the Bank)
 Name and designation of the officer
 Seal, name & address of the Bank and address of the Branch



Contd.....12/-

PERFORMANCE BANK GUARANTEE FORMAT**HQ CE (P) Dantak Enq No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026**

From:

Bank _____

To,

.....

Dear Sir,

1. Whereas you have entered into a supply order No 30003/DTK/19TF/SO- /E3ES dated ____/ /2026 (hereinafter referred to as the said supply order) with _____, hereinafter referred to as the "seller/consignor" for supply of goods as per Part-II of the said supply order to the said seller/consignor and whereas the Seller/consignor has undertaken to produce a bank guarantee for (5%) of total supply order value amounting to _____ to secure its obligations to the HQ CE (P) Dantak. We the _____ bank hereby expressly, irrevocably and unreservedly undertake and guarantee as principal obligors on behalf of the seller/consignor that, in the event that the HQ CE (P) Dantak declares to us that the goods have not been supplied according to the performance obligations under the aforementioned supply order, we will pay you, on demand and without demur, all and any sum up to a maximum of _____ (Rupees _____ only). Your written demand shall be conclusive evidence to us that such repayment is due under the terms of the said supply order. We undertake to effect payment upon receipt of such written demand.

2. We shall not be discharged or released from this undertaking and guarantee by any arrangements, variations made between you and the Seller/consignor, indulgence to the Seller/consignor by you, or by any alterations in the obligations of the Seller/consignor or by any forbearance whether as to payment, time performance or otherwise.

3. In no case shall the amount of this guarantee be increased.

4. This guarantee shall remain valid for months from the date of acceptance of consignment in India/Bhutan or until all the store, spares and documentation have been supplied according to the performance obligations under the said supply order at the destination FOR.

6. Unless a demand or claim under this guarantee is made on us in writing or on before the aforesaid expiry date as provided in the above referred supply order or unless this guarantee is extended by us, all your rights under this guarantee shall be forfeited and we shall be discharged from the liabilities hereunder.

7. This guarantee shall be a continuing guarantee and shall not be discharged by and change in the constitution of the Bank or in the constitution of M/s _____.



Contd... 13/-

FORMAT OF CERTIFICATE OF ACCEPTANCEHQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026CERTIFICATE OF ACCEPTANCE

1. Certified that the M/s _____, hereby accepts the supply order No 30003/DTK/19TF/SO- /E3ES dated ____/____/2026 of the against enquiry No 30003/DTK/19TF/ENQ-58/E3ES dated 19 Mar 2026 as per the supply order assigned to them and handed over the same to HQ CE (P) Dantak at _____ hours, on this _____ day of the month _____ in the year two thousand and twenty six.
2. The list of liabilities as on date is placed at annexure to this certificate.
3. Signed on _____ day of _____ two thousand and twenty six.

 REP
 FOR AND ON BEHALF OF
 THE CHIEF ENGINEER PROJECT DANTAK

 REP OF
 M/s _____

Note. This certificate of acceptance will remain in force till the validity of supply order.



Contd... 14/-

HQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026

UNDERTAKING CERTIFICATE

"It is certified that the goods / materials given in the Enquiry No 30003/DTK/19TF/Enq-58/E3ES dt 19 Mar 2026 of HQ CE (P) Dantak will be supplied by me / our firm as export and for use in Bhutan. It is declared that no GST cost has been included by me in the rates quoted in above mentioned enquiry".

Stamp & Signature with date :

Name of the bidder :

Name of firm with address :



Contd... 15/-

HQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026

SELF DECLARATION CERTIFICATE

It is certified that my firm M/s _____ is not under banned from participation in tenders by any Govt. organization of India/Bhutan. In the event of my declaration being found as not true, my bid be cancelled and I will have no objection to it.

Stamp & Signature with date :

Name of the bidder :

Name of firm with address :



Contd... 16/-

HQ CE (P) Dantak Eng No 30003/DTK/19TF/ENQ-58/E3ES dt 19 Mar 2026

TEST CERTIFICATE IN RESPECT OF GEO WEB WALL AND UPVC PIPE

1. Manufacturer test certificate pertaining to under mentioned test be given for each lot of material being supplied:-

(a) **Geocell (with accessories for connecting & anchoring).**

PHYSICAL PROPERTIES			
Parameter	Units	Minimum Required Value	
Cell Depth	mm	200	
Weld Spacing	mm	356	
Expanded cell dimension	Width	mm	259
	Length	mm	224
Expanded Dimension	Width	m	2.59
	Length	m	6.50
Expanded section area	m ²	16.8	
PERFORMANCE PROPERTIES			
Parameter	Test method	Unit	Minimum Required Value
Density	IS 13360 (Part 3)/ ASTM D 1505	g/cm ³	0.9
Environmental stress crack resistance (ESCR), Modulus	IS 17483/ ASTM D 1693	Hours	≥ 3000
Carbon black content	IS 2530/ ASTM D 1603	%	2
Cell wall thickness	IS 13162 (Part 3)/ ASTM D 5199	mm	1.20-1.25
Perforation Area	-	%	10
Seam Peel-Strength Text (N per 25 mm of cell depth)	-	N	350
Standard oxidative induction time	ISO 11357-6	minutes	100
High pressure oxidative induction time	ASTM D 5885	minutes	400
Make	Geosys/ Techfab/ Geoquest/ Maccefferri/ Terrain Geoinfra		

(b) **Geocomposite (710 GSM).**

MECHANICAL PROPERTIES			
Properties	Test method	Unit	Minimum Required Value
Drainage Core			
Type of Product	HDPE Geonet UV stabilized, comprising of integrally connected set of parallel strands		
Thickness at 2 Kpa	EN ISO-9863	mm	4.5
Mass per unit area	EN ISO-9864	g/m ²	710
Tensile strength	EN ISO-10319	kN/m	16
CBR Puncture resistance	EN ISO-12236	N	3000
In Plane permeability	Hydraulic Gradient, i=1 at 100 kPa pressure	l/(m.s)	0.55
			0.45
Filter Layer			
Type of product	Comprising of PP Nonwoven Needle Punched geo textile bonded on either side of drainage core		
Static Puncture Resistance	EN ISO-12236	N	1200
Flow Rate	ASTM D4491	l/m ² /s	50
Characteristic Opening Size	EN ISO-12956	mm	0.22
Retained Properties after UV exposure	ASTM D4355	%	70
Composite Drain			
Type of Product	Geonet + Filter Geotextile on both side		
Width	-	m	2
Length	-	m	20/25/50
Filter Geotextile			
Permittivity	ASTM D 4491	S ⁻¹	1.0
Make	Geosys/ Techfab/ Geoquest/ Maccefferri/ Terrain Geoinfra		

